

REFERENCES

Over the years, we have delivered over 70,000 street lighting fixtures to our customers. The Royal product family is a result of continuous development and its quality interacts with our other range.

APPLICATIONS

Solljus Royal 30W is a direct replacement for 70W HPS and 125W Hg. It is suitable for smaller roads, parking lots and ski and exercise trails.


VERSIONS


Solljus Royal 30W is our standard street light but on request it is available with powers up to 280W and with accessories such as light sensors, DALI, 0-10VDIM, Bluetooth and other optics.

MOUNTING

The fixture is mounted directly on the pole and on all types of arms up to Ø76mm. A built-in bubble level simplifies alignment and the light fixture has built-in power cut-off for maintenance.











ROYAL	30W
Lumen efficiency	150 lm/W
Lumen	4 500 lm (output depending on optics)
Color temperature	4000 K
Color rendering	CRI 80+
LED lifetime	100 000h L70B10
Light source / Driver	Seoul LED / Sosen with 10KV surge protection
Temperature tolerance	-40°C to +50°C
Control	ON/OFF standard (On request: 0-10V, Bluetooth, Dali)
Protection class	IP 66, 3G vibration, class 1, corrosion resistant, IK08
Optics	Individual Ledil lenses 75*150°. (Type II-M, Type III-M, Type IV-S and 20°x100° on request)
Total weight	5,2 kg
Dimensions	579x253x128 mm

